




RoHS



P.C.B Layout(Pattern side)



规格说明:Specifications

电气特性:Electrical

- 1.额定电流:Current Rating
1.5A/contact terminal
- 2.额定电压:Voltage Rating
30V DC
- 3.接触阻抗>Contact Resistance
50 milliohms Max
- 4.耐电压:Dielectrnic Withstanding Voitage
AC 500V/1MINUTE.
- 5.绝缘阻抗:Insulation Resistance
1000MEGA Ohms Min

物理性能:Mechanical

- 1.插拔力:Connector Mate and Unmate Force
Insertion force:35N(3.57kgf)MAX
Extraction force:10-35N(1.02-3.57kgf)Min
端子保持力:Terminal Retention
1.0kgf(MIN)
耐久性:Durability
5000cycles.EXTRACTLON FORCE:
10-35N(1.02-3.57kgf)

③	Terminal		4	Brass	Silvering
②	Shell		1	SPCC	Ni Plating
①	Base		1	LCP	White
NO.	Name	Number	Qty	Materil	Remarks

YUANDI®
Yuandi Electronics Co,Ltd

design	date	name	USB CONNECTOR
Review	date		
Approved	date		
number		model	USB90-16-T1-W1

							angle	±2°
							10~30	±0.30
							5~10	±0.20
							~ 5	±0.10
				modify	Review	Approved	Tolerance not	specified